


Instrument Data Sheet

General	1	Product	Safety Stop Switch / Pull Cord Switch
	2	Model Number	RS-5
	3	Manufacturer	Conveyor Components Company
	4		
Environment	5	Certified Ambient Temperature Rating	40 °C [104 °F]
	6	Functional Ambient Temperature	-50 to 40 °C [-58 to 104 °F] (increased actuation force may be required below -30 °C [-22 °F])
	7	Enclosure Material	319 cast aluminum
	8	Enclosure Rating (UL)	NEMA Type 1, 3, 3R, 4, 4X
	9	Enclosure Rating (CSA)	Type 3, 4, 4X
	10	Mounting	3 holes at $\varnothing^{13/32}$ " [10 mm] (Vertical surface mounting is standard, bracket available for horizontal surfaces)
	11		
Switch	12	Switch Type	DPDT x 2
	13	Contact Type	Dry contact
	14	Contact Rating	15 A @ 125 or 250 VAC; ¾ hp @ 125 VAC; 1 ½ hp @ 250 VAC
	15	Electrical Action	Latching (via actuator)
	16	Electrical Connection	¾" NPT x 3
	17	Indicating Lamp	None
	18		
	19		
Actuator	20	Type	Pull cord switch
	21	Cable Length	Maximum 100' [30.5 m] on each side of the unit (maximum 200' [61 m] total)
	22	Cable Material	$\varnothing^{3/32}$ " [2 mm] 7x7 galvanized aircraft cable: orange vinyl or nylon coated to $\varnothing^{3/16}$ " [5 mm] OD
	23	Mechanism	Lever with rotating cam
	24	Non-activated Position	Rotated fully clockwise
	25	Activated Position	Rotated fully counterclockwise
	26	Range of Travel	60° counterclockwise from non-activated position
	27	Action	Latching (To reset, push lever inward and rotate clockwise)
	28	Actuation Force	Field adjustable
	29		
Options	30	Finish	Uncoated (standard) or epoxy coating (option E)
Accessories	31	Safety Cable	Orange vinyl (RS-25) or nylon (RS-26) coated cable available
	32	Cable Support Eye Bolt	RS-27: \varnothing 1" [25mm] eye X 6" [150 mm] long, with 2 hex-nuts and 1 lock washer
	33	Cable End Fitting	RS-28
	34	Conduit Plug	RS 29: ¾" metal conduit plug; square head
	35	Mounting Bracket	RS-30 available for horizontal surface mount
	36		
Certifications	37	UL Certification File	E83971
	38	CSA Certification File	71174
	39		
Manufacturer	40		
Notes: 1. Cable must be supported with eyebolts. Maximum spacing: 10' [3 m]. 2. Maximum of 100' [30.5 m] of cable may be attached to each side of the unit; 200' [61 m] total.			